



Certified to ISO 9001:2015 TÜVRheinlar





## **Product Data Sheet**

## **Counter-Top Protection Film - Heavy Duty**



## **Product Descripton:**

This product is a temporary protective mask designed for use on semi-smooth surfaces. It is excellent for protection of polished #3 and #4 stainless steel, painted aluminum, and similar surfaces.

	Backing:	Low Density Polyethylene Film
	Adhesive:	Acrylic Adhesive
	Color(s):	Clear
	Tack Level	Low
Item ID Numbers Here: CTPF24600CH,	Tensile Strength:	11 lbs/sq. in (PSTC-131)
CTPF30600CH	Adhesion to Steel:	2.0-4.0 oz/in (PSTC-101)
	Total Thickness:	3 Mil (PSTC-133)
Wrap-Tite, Inc. 6200 Cochran Rd. Solon, Ohio 44139 Toll Free: 888-WRAP-TITE Fax: 440-349-5432	Elongation (%)	325%
	Holding Power (Maximum)	45 Days
www.wraptite.com - info@wraptite.com	Country of Origin	USA

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.