



Product Data Sheet

Counter-Top Protection Film - Medium Weight



Product Description:

This product is a temporary protective mask designed for use on smooth and semi-smooth surfaces. It is excellent for #3 semi-polished and #4 brushed/satin stainless steel, painted aluminum, and similar surfaces. The film contains a 180-day UVI additive that provides clean removal of the tape after prolonged exposure to sunlight.

| | |
|---------------------------|-------------------------------|
| Backing: | Low Density Polyethylene Film |
| Adhesive: | Acrylic Adhesive |
| Color(s): | Clear |
| Tack Level | Low |
| Tensile Strength: | 11 lbs/sq. in (PSTC-131) |
| Adhesion to Steel: | 2.0-4.0 oz/in (PSTC-101) |
| Total Thickness: | 2.5 Mil (PSTC-133) |
| Elongation (%) | 325% |
| Country of Origin | USA |

Item ID Numbers

Here: CTPF24600CM,
CTPF30600CM

Wrap-Tite, Inc.
6200 Cochran Rd.
Solon, Ohio 44139
Toll Free: 888-WRAP-TITE
Fax: 440-349-5432
www.wraptite.com -
info@wraptite.com

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.