



# FLAT BACK TAPE



## Product Data Sheet

Effective 12/2019

### Product Description:

An aggressive pressure sensitive flatback with an adhesive that has been specifically designed to offer a strong and secure seal on a variety of substrates. This product is not repulpable.

### Product Application:

Carton sealing, packaging, light duty splicing. tabbing and picture framing

Item ID: FBT6048, FBT6072



### Nominal Values:

Backing	Kraft Flatback	
Adhesive	Synthetic Rubber	
Total Thickness:	5.5 mil	(PSTC -133)
Adhesion to Steel:	85 oz/in	(PSTC 101)
Tensile Strength:	34 lb./in	(PSTC-131)
Elongation (% at break)	3	
Color	<b>Brown</b>	

(Tolerance +/- 10%); We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

**Wrap Tite, Inc.**  
 6200 Cochran Rd.  
 Solon, Ohio 44139  
**Toll Free:** 888-WRAP TITE (972-7848)  
**Fax:** 440-349-5432  
[www.wraptite.com](http://www.wraptite.com) - [info@wraptite.com](mailto:info@wraptite.com)

